



#### Main features

- Ability to control up to four cursors simultaneously
- Two M12 connectors for simplified connection to Profibus, one M8 connector for separate power connection (transducer can be powered without having to connect it to the bus)
- Local intelligence
- Profibus DPV0 interface on RS485 in conformity to IEC 61158
- Strokes from 50 to 4000 mm
- Displacement position settable via software up to 5  $\mu\text{m}$
- Speed resolution up to 0.01 mm/sec
- Linearity error 0.01%
- Repeatability error 0.001%
- Resistance to vibration (DIN IEC68T2/6 12 g)
- IP67 protection

Contactless absolute linear displacement transducer with magnetostrictive technology.

The Profibus fieldbus communication interface permits integration in complex systems with large communication distances, guaranteeing safe and rapid data transmission. The contactless cursor eliminates problems of wear, for almost unlimited transducer life. The countless advantages include reduced size for easier installation, high protection level for use in harsh environments, high performance in terms of linearity, repeatability, and resistance to vibration and impact, to assure maximum reliability.


#### TECHNICAL CHARACTERISTICS

Model	from 50 to 4000 mm
Measurement read	Displacement
Displacement sampling time (typical)	1 ms
Shock test DIN IEC68T2-27	100g - 11ms - single blow
Vibrations DIN IEC68T2-6	12g / 10...2000Hz
Displacement speed	$\leq 10$ m/s
Max. acceleration	$\leq 100$ m/s <sup>2</sup> displacement
Resolution	up to 5 $\mu\text{m}$
Cursor type	Sliding cursor Separate floating cursor
Working temperature	-30...+75°C
Storage temperature	-40...+100°C
Temperature coefficient	20ppm FS / °C
Ambient protection	IP67

#### ELECTRICAL CHARACTERISTICS

Output signal	Profibus DPV0 su RS485
Rated power supply	24 Vdc $\pm 20\%$
Max. power ripple	1Vpp
Max. input	100mA
Min. load on output	RS485 standard
Electrical isolation	500 V (D.C. power/ground)
Protection against reversed polarity	YES
Protection against overvoltage	YES
Self-resetting internal fuse	YES


#### MECHANICAL DIMENSIONS



ELECTRICAL / MECHANICAL DATA

Model		50	75	100	130	150	175	200	225	250	300	350	360	400	450	500	550	600	650	700	750	800	850	900	950	1000	1100	1200	1250	1300	1400	1500	
																						1750	2000	2250	2500	2750	3000	3250	3500	3750	4000		
Electrical stroke	mm	Model																															
Independent linearity	± %F.S.	Typical 0,02 (Max. 0,04)																															
Max. dimensions (A)	mm	Model + 194																															
Repeatability	mm	< 0,01																															
Hysteresis	mm	< 0,01																															
Minimum sampling time	ms	1 for strokes from 0 to 1200mm; 2 for strokes from 1200 to 2400mm; 4 for strokes > 2400mm																															

ELECTRICAL CONNECTIONS AND CONFIGURATION OF LEDs

MK4P W OUTPUT		CONNECTOR A (M12 FEMALE)		CONNECTOR B (M8 MALE)		CONNECTOR C (M12 MALE)	
		1	5VD_ISO	1	24V	1	5VD_ISO
		2	LINE_A/N	2	N.C.	2	LINE_A/N
		3	GND_ISO	3	0V	3	GND_ISO
		4	LINE_B/P	4	N.C.	4	LINE_B/P
		5	GROUND			5	GROUND
		GREEN LED (ON)		RED LED (System Fault)		RED LED (Bus Fault)	
		CODE					
Off		Off		Off		Device not powered	
On		On		On		Internal device error (incorrect initialization)	
On		Off		On		Master not connected to network	
On		On		Off		Correct initialization	
On		On/Off		Flashing (f=1Hz)		Network error, master not connected to network	
On		Off		Off		Incorrect number of magnets	
						Magnet out of measurement range	
						Internal device error	
						Master connected to network	
						Incorrect parameterization or configuration	
						Device in data exchange	


PROFIBUS AND CONNECTION STRUCTURE

A Profibus network lets you connect peripheral devices defined as Slaves (transducers or actuators) to main control units defined as Class 1 Masters (typically PLCs).


The network software is installed by means of a Class 2 Master containing the database with the GSD files of all connected devices. The network is drawn and parameterized with a graphics tool, then the configuration is loaded in the Class 1 Masters in the network. The Class 1 Master(s) launch(es) the communication process with the peripheral devices according to the configuration received from the Class 2 Master.

This process includes an exchange of initial data regarding identification of the Slaves and their parameterization and configuration. When this phase is done, control of the application begins with an exchange of process data on the network.

The GSD file contains all of the data on device identification, supported functions, and length and format of data packets



- Connection with two M12 connectors  
+ 1 M8 connector:
- no T connection needed
  - standard M12 and M8 connectors
  - separate power supply line (ideal for use of programmer)



ORDER CODE

Displacement transducer

MK4PW

Model

1 cursor	1
2 cursors	2
4 cursors	4

Configurator

0002XXXX00X0XX

Node number programmer

XXX = standard; node = 125  
nnn = Node number specified in order

0	No certificate to be attached
L	Linearity curve to be attached

Ex.: MK4-P-W-0400-2 0000-2-PXXX-00-X-0-XX

Model MK4 transducer, Profibus DP output, 2 M12 connectors + 1 M8 connector, model 400, 2 cursors, system resolution 0.005 mm, node number to be specified in order .

CURSORS AVAILABLE ON REQUEST

PCUR

Cursors	
Sliding cursor, axial joint (low) (STANDARD)	035
Sliding cursor, axial joint (high)	036
Sliding cursor, angular joint	037
Floating cursor	034

PCUR035

PCUR036

PCUR037

PCUR034

BRACKETS AVAILABLE ON REQUEST

PKIT

Brackets (2 brackets for every kit)	
Steel bracket, distance between centers 42.5 mm	090
Steel bracket, distance between centers 50 mm	091

Bracket code	Distance between center (l)	Thread (M)	Dimensions (A)
PKIT090	42.5	M4	56
PKIT091	50	M5	63.5

## OPTIONAL CABLES

M8 axial 4-pin female connector, prewired with 3-meter power cable	<b>PCAV700</b>
M8 axial 4-pin female connector, prewired with 5-meter power cable	<b>PCAV701</b>
M12 axial 5-pin female connector, prewired with 3-meter communication cable	<b>PCAV702</b>
M12 axial 5-pin female connector, prewired with 5-meter communication cable	<b>PCAV704</b>
M12 axial 5-pin male connector, prewired with 3-meter communication cable	<b>PCAV703</b>
M12 axial 5-pin male connector, prewired with 5-meter communication cable	<b>PCAV705</b>

## OPTIONAL ACCESSORIES

Profibus terminator (M12 axial male connector)	<b>CON049</b>
M12 axial 5 pin male connector	<b>CON380</b>
M12 axial 5 pin female connector	<b>CON390</b>
Node number programmer	<b>XXXXXX</b>
GSD file downloadable from website <a href="http://www.gefran.com">www.gefran.com</a>	

Sensors are manufactured in compliance with:

- EMC 2004/108/CE compatibility directive
- RoHS 2002/95/CE directive

Electrical installation requirements and Conformity certificate are available on our web site: [www.gefran.com](http://www.gefran.com)

**GEFRAN spa** reserves the right to make aesthetic or functional changes at any time and without notice

**GEFRAN**

**GEFRAN spa**  
via Sebina, 74  
25050 PROVAGLIO D'ISEO (BS) - ITALIA  
ph. 0309888.1 - fax. 0309839063  
Internet: <http://www.gefran.com>

DTS\_MK4P\_0709\_ENG